

**Khyam**  
**Weather Weave 5000**  
**Camper Awning**  
Quick set up guide.

Please note that this 'quick set up guide' is designed to help familiarise you with the tents features, general set up and to help you check the tent prior using it for the first time. This guide is not intended as a replacement to the main instructions and we strongly recommend that you study the main instructions supplied before erecting your tent.

### **Safety First**

- Never use combustible fuels inside your tent.  
( Gas/Petrol/Mentholated Spirits etc - lights/cookers/heaters)  
Remember tents can burn.  
Do not smoke.
- Do not use naked flames except in designated cooking areas.  
Try to locate this tent at least 6 m from other campers.  
Know the site's safety procedures  
Keep all exits clear.  
Camp Safely.

### **Before Use**

- Please check the contents, erect and pitch your tent fully before embarking on your first camping holiday. In the unlikely event of finding any manufacturing defects or missing items please rectify this with your local dealer before going away.
- Be careful to avoid pitching your tent over sharp stones etc as this may damage the groundsheets. Pitching under trees may cause the flysheet to be contaminated with sap, this is not only impossible to remove but may also damage the flysheet.

### **Tent Limitations**

Tents are designed to be lightweight and packable and therefore require care and understanding in their use. Whilst the outer Flysheet is waterproof, driving rain can, in some cases, cause water ingress around vents, zips and seams. You will get a certain amount of condensation build up. This is caused by the relatively warmer, humid air inside the tent making contact with colder outer fabric of your tent. This should not be confused with leakage. Please take particular care when assembling your tent in windy conditions. Ensure you have others to help you. If you overstress poles, they will break. Your local retailer can supply replacement / spare pole sections. Always pitch your tent securely and ready for all weather conditions using all pegs and guys. The standard pegs supplied with this tent are suitable for normal ground conditions, however rocky, boggy, sandy or loose soil may require specialist pegs which are available through your local retailer. It is advisable to have some of these pegs to hand for use should you encounter such ground conditions on your trip. Never push pegs in by hand use a wooden or rubber faced mallet. Make sure your tent and personal belongings are insured. We accept no liability for consequential damage. Storm damage is not covered under our guarantee. Never pack your tent away wet or store your tent in a wet or damp conditions, it will get mildew. If you have to pack down in the rain ensure the tent is thoroughly dry before repacking.



### **Assembly**

Please note these instructions are guidelines only and we recommend reading and studying the main instructions fully before using your tent for the first time.

- 1/ Try to position your vehicle and awning so the opening of the awning is facing away from the prevailing wind. Around the base you will see webbing loops with metal rings, these secure the poles of the awning to the base of the flysheet.
- 2/ Assemble all the steel poles supplied. Thread the pre-curved roof pole through the sleeves on the flysheet.
- 3/ Locate the steel upright poles. Starting on one side of the tent locate the end ferrule of the upright pole into the open end of the roof pole. Locate the pin on the ring at the base of the flysheet up inside the bottom section of the same steel pole, ensuring the flysheet sleeves are not caught anywhere as the tension created may cause damage to the flysheet if they are trapped. Repeat this on the remaining pole on the opposite side of the tent. Once both poles are located the side pole clips on each side can be fixed into place.
- 4/ With all poles in place and located, place the awning in the desired position along side your vehicle.
- 5/ Please take great care when fitting the awning to your vehicle. Ensure that the poles and fittings of the awning do not fall against your vehicle. We recommend that a second person holds the framework of the awning whilst you fit the awning to your vehicle. For further fitting instructions please refer to the main instructions supplied with your awning.
- 6/ Gently pull the front of the awning outwards so it starts to take shape and guy down via the guy ropes on the front of the awning.
- 7/ Peg out all remaining pegging points and guy lines and adjust as necessary, do not over tension guy lines this will distort the poles making the tent unstable.

### **After Care**

Always clean off mud and grass before packing. Always dry your tent thoroughly before storing. Store in dry well ventilated conditions. Treating the outer fabric with a proofing spray at regular intervals will prolong the life of your tent.